

Pit Start Plus

Car wash start systems



The best-in-class device for activating self-service washing bays

suzohapp.com

The Ideal Solution for Self-service Washing Bays

Specifically designed for self-service washing bays, it manages up to 7 wash programs through a single payment unit. Solid and resistant, it guarantees excellent protection against dust, water jets and nebulised chemical products. Pit Start Plus is available in 2 different versions for easy installation. Suitable for modernising existing high-pressure systems which employ electro-mechanical control systems.

Features

- IP 54 protection degree
- Coin entry protected by a mobile plate
- Stainless steel external frame, door and pushbutton panel
- Opening protected by a fully waterproof 4-point closing lock, equipped with an anti-drilling plate
- Back-lit display for maximum visibility even in conditions of full sunlight
- Pushbutton panel equipped with 7 program selection buttons and 1 stop button, which allows the user to interrupt the service in progress
- Front panel with wide space for user's instructions, shown on a customisable adhesive panel
- In the standard version, the interface is made with a DIN guide box equipped with 8 opto-isolated inputs for receiving signals from the system control unit and 7 relay outputs
- Prices of the services can be set on-board machine
- Installation: free standing or wall mounted

Functions

Stand-by status

Technical Schematics


to or higher than the lowest configured price, the Pit Start Plus is ready to activate the relative service


1469 1508



Note: Unit of measure mm

© 2019 SUZOHAPP. All rights reserved. Specifications subject to change. 08-26-19







Installed peripherals

- RM5 HD electronic coin validator
- EuroKey Next cashless system

Optional peripherals

- NV9 USB banknote reader
- WorldKey cashless system

Wall-mounted starter

Contactless POS

Technical specifications

Free	stand	ing	sta	rtei
	0.0011.101		0.00.	

reenned speemedtons	rice stariarity starter		Wait fillouffied starter	
Dimensions (LxHxW)	394 x 1,508 x 283 mm		388 x 688 x 182,3 mm	
Weight	52 kg		17 kg	
Power supply	24 Vac ±10%		24 Vac ±10%	
Power consumption	25 W		25 W	
Operating temperature	-15 °C ÷ 50 °C humidity 10% ÷ 90% non-condensed		-15 °C ÷ 50 °C humidity 10% ÷ 90% non-condensed	
Coin Capacity	0.5€	1€		2€
Cash box	800	850		650



suzohapp.com